



# ENHANCED Compatibility. Exceptional Comfort.

## **KEY FEATURES**

- Cushioned metal headband provides durability while maintaining a comfortable, secure fit.
- Leatherette ear cushions fold flat for easy storage.
- Noise-canceling mic with flexible boom.
- Call answer/end, mute, volume +/-.
- Variants include universal USB or USB-C type connectivity.
- 3.5 mm connectivity lets you work on a variety of mobile devices.

## **BLACKWIRE' 5200 SERIES**

The Blackwire 5200 Series fits your busy workday. Easy to use, its USB or USB-C and 3.5 mm connectivity lets you work on a variety of devices. Ergonomically designed, it's comfortable enough to wear all day, on your longest calls. The Blackwire 5200 Series — the power to connect and work easily is here.

#### **TOP FEATURES**

- Ideal for all-day use, long conference calls and listening to multimedia.
- Noise canceling microphone masks nearby talkers for maximum call privacy.
- Available in monaural (Blackwire 5210) or hi-fi stereo with passive noise reduction (Blackwire 5220).
- Variants include universal USB or USB-C.
- Connectivity to smartphone and tablet via 3.5 mm.
- One-touch call answer/end, volume +/- and mute.
- PC wideband audio with noise-canceling microphones for high-quality PC telephony.
- Plantronics Manager Pro, an additional purchase, enables your IT team to gain insight into every compatible Plantronics headset being used company-wide.

# BLACKWIRE<sup>®</sup> 5200 SERIES

BLACKWIRE 5210 (MONAURAL)





## SPECIFICATIONS

#### **CONNECTS TO**

• PC via USB/USB-C, connects to mobile devices and tablets via 3.5mm and devices that support USB-C

#### **IDEAL FOR**

• Users with extensive PC communication and multimedia

#### **AUDIO PERFORMANCE**

- Dynamic EQ
- Microphone frequency response 100 Hz-8 kHz optimal for PC wideband voice telephony (up to 6,800 Hz)
- Hi-fi stereo (C5220, C5220 USB-C only) receive frequency response from 20 Hz-20 kHz
- Enhanced Digital Signal Processing (DSP)
- Noisecanceling microphone
- Adjustable audio alerts with Plantronics Hub software (mute/volume)<sup>1</sup>

#### **HEARING PROTECTION**

- SoundGuard<sup>®</sup> DIGITAL protects against sound levels above 118dBA
- Anti-startle (during calls) detects and eliminates any large sudden increase in signal level
- Time-Weighted Average prevents average daily noise exposure from exceeding 85 dBA (enabled by Plantronics Hub).
- Additional lower level hearing protection against acoustic startle is provided by Plantronics Hub software limiting peak levels to 102 dBA

#### MODELS

- C5210 USB (Monaural)
- C5210 USB-C (Monaural)
- C5220 USB (Stereo)
- C5220 USB-C (Stereo)
- Built for UC applications and softphones from Avaya<sup>®</sup>, Cisco<sup>®</sup>, Microsoft<sup>®</sup> and more.<sup>1</sup>
- Certified for Skype for Business

#### **INCLUDED ACCESSORIES**

• Carrying case for easy storage and portability



#### WEIGHT (WITH CABLE)

• 125.4 g/0.28 lbs

#### WEIGHT (WITHOUT CABLE)

• 100 g/0.22 lbs

## CABLE LENGTH (INLINE MODULE TO HEADSET)

• 1160 mm/3.81 ft

#### CABLE LENGTH (USB TO INLINE MODULE)

• 940 mm/3.08 ft

#### **CABLE LENGTH (TOTAL USB TO HEADSET)**

• 2170 mm/7.12 ft

#### **HEADBAND ADJUSTMENT**

• 40 mm/0.13 ft

#### **BOOM ROTATION**

• 280°

#### **SPEAKER SIZE**

• 28 mm/0.09 ft

## WEIGHT (WITH CABLE)

• 164.2 g/0.36 lbs

## WEIGHT (WITHOUT CABLE)

• 138.8 g/0.31 lbs

#### CABLE LENGTH (INLINE MODULE TO HEADSET)

• 1160 mm/3.81 ft

## CABLE LENGTH (USB TO INLINE MODULE)

• 940 mm/3.08 ft

#### CABLE LENGTH (TOTAL USB TO HEADSET)

• 2170 mm/7.12 ft

#### **HEADBAND ADJUSTMENT**

• 52 mm/0.17 ft

#### **BOOM ROTATION**

• 280°

#### **SPEAKER SIZE**

• 28 mm/0.09 ft

#### **INPUT IMPEDANCE**

• 32Ohms

#### **SPEAKER SENSITIVITY**

• 90<sup>2</sup>

#### SPEAKER BANDWIDTH (SPEECH MODE)

• 200-6800Hz

## SPEAKER BANDWIDTH (MEDIA MODE)

• 20-2000Hz

#### MAXIMUM ACOUSTIC OUTPUT

• 118dBSPL

#### **MICROPHONE SENSITIVITY**

• -38dBV/Pa

#### **MICROPHONE BOOM LENGTH**

• 122.5 mm/0.40 ft

#### **MICROPHONE BANDWIDTH**

• 100-10000Hz

#### **INPUT IMPEDANCE**

• 320hms

#### **SPEAKER SENSITIVITY**

• 90<sup>2</sup>

## SPEAKER BANDWIDTH (SPEECH MODE)

• 200-6800Hz

## SPEAKER BANDWIDTH (MEDIA MODE)

• 20-20000Hz

## MAXIMUM ACOUSTIC OUTPUT

• 118dBSPL

## **MICROPHONE SENSITIVITY**

• -38dBV/Pa

## **MICROPHONE BOOM LENGTH**

• 122.5 mm/0.40 ft

## MICROPHONE BANDWIDTH

• 100-10000Hz

<sup>1</sup> Download the latest release of Plantronics Hub software to get one-touch call answer/end with these softphones.

 $^{2}1mW/1kHz$  0.01m open field

## LEARN MORE

For more information on Blackwire 5200 Series visit www.poly.com

